

HOT SHOT SERIES



4230-20G1

**BUY 6 +
SAVE 2%***



2115-15G1

HOT SHOT MINI SERIES

STANDARD FEATURES

- Rugged powder coated steel frame
- 4-wheel dimensions: 39"L x 31"W x 49"H, 2-wheel dimensions: 44"L x 27"W x 36"H
- Super efficient schedule 80 coil w/ one-piece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade motors
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor (prevents over heating in bypass mode)

NOTE: 115V units include GFCI with 35' cord, 230V units include 12' cord (no plug). All units are completely factory assembled, tested in the USA, and delivered ready to operate.

STANDARD ACCESSORIES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo 20% chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

AVAILABLE OPTIONS: ALL MODELS

ATK010 Inline Adjustable Thermostat.
List: \$204.92

AVAILABLE OPTIONS: 4 WHEEL MODELS ONLY

BRK100 Brake Kit. List: \$76.24
HRK415 Hose Reel Kit, 150' x 3/8" max. w/ no add'l hose. List: \$328.98
CAT pumps available - consult factory

2 WHEEL PORTABLE DIRECT DRIVE ELECTRIC MODELS

2115-15G1	2.0 GPM @ 1500 PSI	2.0 HP	115V/1PH/18A	GP Pump
3115-10G1	3.0 GPM @ 1000 PSI	2.0 HP	115V/1PH/18A	GP Pump
3230-15G1	3.0 GPM @ 1500 PSI	3.0 HP	230V/1PH/12A	GP Pump

4 WHEEL PORTABLE DIRECT DRIVE ELECTRIC MODELS

3230-30A1	3.0 GPM @ 3000 PSI	6.0 HP	230V/1PH/26A	AR Pump
4230-20G1	4.0 GPM @ 2000 PSI	6.0 HP	230V/1PH/26A	GP Pump
4230-25G1	3.5 GPM @ 2500 PSI	6.0 HP	230V/1PH/26A	GP Pump
4230-30G1	3.5 GPM @ 3000 PSI	7.5 HP	230V/1PH/35A	GP Pump
5230-30A1	5.0 GPM @ 3000 PSI	10 HP	230V/1PH/44A	AR Pump
4230-35A1	4.0 GPM @ 3500 PSI	10 HP	230V/1PH/44A	AR Pump
4230-40A1	3.5 GPM @ 4000 PSI	10 HP	230V/1PH/44A	AR Pump

***BUY 6 + OF ANY MACHINE & SAVE 2% - NO MIX & MATCH**

WWW.PRESSUREWASHERSAREA.COM