

PRO POWER SERIES



PPS3030HCI

**BUY 6 +
SAVE 2%***

PRO POWER MODELS

PPS2527HAI	2.5 GPM @ 2700 PSI	GC190	Honda	AR RMV-A Pump/Int UL
PPS2527LAI	2.5 GPM @ 2700 PSI	PP208	LCT	AR RMV-A Pump/Int UL
PPS2530HAI	2.5 GPM @ 3000 PSI	GC190	Honda	AR RMV-B Pump/Int UL
PPS2630HGI	2.6 GPM @ 3000 PSI	GC190	Honda	GP TP Pump/Int UL
PPS2630LGI	2.6 GPM @ 3000 PSI	PP208	LCT	GP TP Pump/Int UL
PPS3030HCI	3.0 GPM @ 3000 PSI	GC190	Honda	CAT 4PPX Pump/Int UL
PPS3030LCI	3.0 GPM @ 3000 PSI	PP208	LCT	CAT 4PPX Pump/Int UL
PPS2533HAI	2.5 GPM @ 3300 PSI	GX200	Honda	AR RMV-B Pump/Int UL
PPS2533LAI	2.5 GPM @ 3300 PSI	PP208	LCT	AR RMV-B Pump/Int UL
PPS2533HCI	2.5 GPM @ 3300 PSI	GX200	Honda	CAT 4PPX Pump/Int UL
PPS2533LCI	2.5 GPM @ 3300 PSI	PP208	LCT	CAT 4PPX Pump/Int UL
PPS4042HAI	4.0 GPM @ 4200 PSI	GX390	Honda	AR RSV Pump/Int UL
PPS4042LAI	4.0 GPM @ 4200 PSI	PP414	LCT	AR RSV Pump/Int UL
PPS4042HCI	4.0 GPM @ 4200 PSI	GX390	Honda	CAT 67DX Pump/Int UL
PPS4042LCI	4.0 GPM @ 4200 PSI	PP414	LCT	CAT 67DX Pump/Int UL
PPS4042HGI	4.0 GPM @ 4200 PSI	GX390	Honda	GP TX Pump/Int UL
PPS4042HG	4.0 GPM @ 4200 PSI	GX390	Honda	HP PEP Pump
PPS4042LGI	4.0 GPM @ 4200 PSI	PP414	LCT	GP TX Pump/Int UL
PPS4042LG	4.0 GPM @ 4200 PSI	PP414	LCT	HP PEP Pump



S/PPS4042LG

SKID MOUNT

STANDARD FEATURES

- Revolutionary aircraft grade aluminum frame with dual handles (no welds to fail)
- Lifetime frame warranty
- 50 mesh inlet filter
- Adjustable pressure unloader
- Low oil shutdown LCT & GX models only
- Pneumatic tires
- Dual padded shock absorbing feet
- 3/4" cold-rolled steel axle
- Honda GC Series consumer grade & GX Series commercial grade engines are 50 state approved
- LCT Maxx Series commercial grade 49 state approved engines - **Not available in CA.**
- Thermo-sensor (prevents overheating in bypass mode)

NOTE: Units are completely factory assembled, tested in the USA, and delivered ready to operate. All models meet or exceed PWMA standards of +/- 10%.

STANDARD ACCESSORIES

- Gun/wand assembly
- 25' hose w/ couplers*
- Chemical injector
- 3 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

***NOTE:** 2700-3300 PSI models include 22mm twist coupler socket hose ends; 4200 PSI models include 22mm twist socket x 3/8" QC plug hose ends.

AVAILABLE OPTIONS

ALL MODELS:

Skid Mount - precede model with S/, Example: S/PPS4042LAI.

50' Hose Upgrade - add -50 suffix to model, Example: PPS2532LAI-50 List: \$55

AVAILABLE OPTION

PP208, GC190, & GX200 ENGINE MODELS ONLY:

UPS-Shipping Carton: No Extra Charge Includes: Specially designed protective carton and contractor grade two piece gun-wand assembly. Order standard model and add UPS suffix after model. Example: PPS2532LAI-UPS

NOTE: UPS models require minor assembly.