



**RENTAL TESTED.**  
**BOUGHT BY PROFESSIONALS.**

# SNG Series

## Hot Water Pressure Washer Electric Powered | Natural Gas | Belt Drive

For indoor cleaning with hot water, the Shark SNG pressure washer is the most compact and versatile solution available. It packs cleaning power of up to 10 GPM, yet has a small footprint (24" x 49" or 35" x 64"). Heated by natural gas, the long lasting SNG burner has no moving parts, which reduces wear and tear. Optional auto start/stop control at the gun makes for speedy cleaning, and optional two gun operation allows multiple users to clean at the same time. Remote cleaning stations can be conveniently added throughout any shop. The SNG is the ideal solution for reliable, but affordable, hot water cleaning indoors.

Durable **hot water coil** made of 1/2-inch, Sch. 80 steel pipe and cold rolled for years of leak-free operation; with **easy coil access** design

Overload protected **control switches** with adjustable thermostat, hour meter and switches for burner and pump

Ventilated **steel cabinet** with **Cool Wall construction** keeps cabinet cool to the touch

**Two gun operation capability** speeds cleaning of heavily soiled equipment

Easy-to-understand illustrated **operating instructions** in English, Spanish and French for multi-lingual operator and owner protection

Three **quick-couple nozzles** are made of hardened stainless steel and mounted for quick access

**Quick-release couplers** and **tangle-free, swivel crimp fitting** positioned on hose for ease of operation

**Forklift guides** for convenience in installation and moving within the shop

Heavy-duty, insulated **trigger gun** with fatigue-free handle and rated for 4500 PSI

Comes with Insulated 36" **stainless steel wand** and 50 ft. of **single wire high-pressure Tuff Skin hose** and fatigue-free **trigger gun**

**Safety thermal pump saver valve** protects against hot-water damage by venting recirculated water

**Safety rupture disk** attached to discharge side of heating coil protects against excessive pressure

High-quality **unloader valve** for operational safety

**Small footprint!**



Dimensions: 49" x 24" x 48" or 64" x 35" x 61"



Industrial-grade, triplex, oil-bath, belt-drive **high-pressure pump**, with three ceramic pistons and forged brass manifold, backed by a limited 7-year warranty; features a cast-iron **pulley system** with "Tru-Tite" **self-tensioning belt** for long life and easy maintenance on pump

Six **removable panels** allow easy access to components for service or repair

Reinforced, nylon fiberglass **float tank** with overflow line and **diaphragm float valve** - no float ball or lever arm to get in the way

High-efficiency **burner** with **electronic ignition** standard on all models, eliminating the hassle of constantly lighting the pilot flame

"**Felder's Choice**" **inlet/outlet connections** provide ability to have inlet/outlet connections on either side of machine for flexibility in installation

Industrial-duty **Baldor electric motor** with multiple voltage options and thermal overload protection

All Shark production plants are ISO 9001 certified



Certified to UL-1776 Safety Standards



Optional **Wireless Remote** controls the pump, burner and detergent up to 300 feet away, while avoiding the hassle and expense of electrical installation for remote workstations.



Swing out burner ring and "Stay in Place" pilot assembly (not attached to burner ring) for easy inspection and repair



Larger Model  
6-10 GPM

Smaller Model  
3.5-5 GPM



**RENTAL TESTED.**  
**BOUGHT BY PROFESSIONALS.**

MODEL	ORDER NO.	GPM	PSI	NOZZLE	MOTOR HP	PUMP	VOLTAGE	PHASE	AMPS	BTU	DIMENSIONS	SHIP WT
SNG4-20024A	1.109-874.0	3.5	2000	5	5	KD4020R	230V	1 ph	25	310,000	49"x24"x48"	815 lbs
SNG4-22024A	1.109-875.0	4	2200	5.5	6.2	KM4035R	230V	1 ph	29	364,000	49"x24"x48"	843 lbs
SNG4-22024B	1.109-876.0	4	2200	5.5	6.2	KM4035R	230V	3 ph	16	364,000	49"x24"x48"	843 lbs
SNG4-22024C	1.109-877.0	4	2200	5.5	6.2	KM4035R	460V	3 ph	7	364,000	49"x24"x48"	843 lbs
SNG4-22024F	1.109-878.0	4	2200	5.5	6.2	KM4035R	575V	3 ph	6.5	364,000	49"x24"x48"	843 lbs
SNG4-22024G	1.109-879.0	4	2200	5.5	6.2	KM4035R	208V	1 ph	30	364,000	49"x24"x48"	843 lbs
SNG4-22024H	1.109-880.0	4	2200	5.5	6.2	KM4035R	208V	3 ph	18	364,000	49"x24"x48"	843 lbs
SNG4-30024A	1.109-881.0	3.9	3000	4.5	8.2	KM4035R	230V	1 ph	36	354,000	49"x24"x48"	856 lbs
SNG4-30024B	1.109-882.0	3.9	3000	4.5	8.2	KM4035R	230V	3 ph	25	354,000	49"x24"x48"	856 lbs
SNG4-30024C	1.109-883.0	3.9	3000	4.5	8.2	KM4035R	460V	3 ph	11	354,000	49"x24"x48"	856 lbs
SNG4-30024F	1.109-884.0	3.9	3000	4.5	8.2	KM4035R	575V	3 ph	14	354,000	49"x24"x48"	856 lbs
SNG4-30024G	1.109-885.0	3.9	3000	4.5	8.2	KM4035R	208V	1 ph	38	354,000	49"x24"x48"	856 lbs
SNG4-30024H	1.109-886.0	3.9	3000	4.5	8.2	KM4035R	208V	3 ph	27	354,000	49"x24"x48"	856 lbs
SNG5-23024A	1.109-887.0	5	2300	6.5	8.2	KT5030R	230V	1 ph	36	439,000	49"x24"x48"	856 lbs
SNG5-23024B	1.109-888.0	5	2300	6.5	8.2	KT5030R	230V	3 ph	25	439,000	49"x24"x48"	856 lbs
SNG5-23024C	1.109-889.0	5	2300	6.5	8.2	KT5030R	460V	3 ph	11	439,000	49"x24"x48"	856 lbs
SNG5-23024F	1.109-890.0	5	2300	6.5	8.2	KT5030R	575V	3 ph	14	439,000	49"x24"x48"	856 lbs
SNG5-23024G	1.109-891.0	5	2300	6.5	8.2	KT5030R	208V	1 ph	38	439,000	49"x24"x48"	856 lbs
SNG5-23024H	1.109-892.0	5	2300	6.5	8.2	KT5030R	208V	3 ph	27	439,000	49"x24"x48"	856 lbs
SNG5-30024A	1.109-893.0	4.8	3000	5.5	10	KT5030R	230V	1 ph	40	415,000	49"x24"x48"	885 lbs
SNG5-30024B	1.109-894.0	4.8	3000	5.5	10	KT5030R	230V	3 ph	26	415,000	49"x24"x48"	885 lbs
SNG5-30024C	1.109-895.0	4.8	3000	5.5	10	KT5030R	460V	3 ph	15	415,000	49"x24"x48"	885 lbs
SNG5-30024F	1.109-896.0	4.8	3000	5.5	10	KT5030R	575V	3 ph	14	415,000	49"x24"x48"	885 lbs
SNG5-30024G	1.109-897.0	4.8	3000	5.5	10	KT5030R	208V	1 ph	49	415,000	49"x24"x48"	885 lbs
SNG5-30024H	1.109-898.0	4.8	3000	5.5	10	KT5030R	208V	3 ph	32	415,000	49"x24"x48"	885 lbs
SNG6-32024B	1.109-899.0	6.3	3200	7	15	KT6035R	230V	3 ph	39	507,000	64"x35"x61"	1825 lbs
SNG6-32024C	1.109-900.0	6.3	3200	7	15	KT6035R	460V	3 ph	19	507,000	64"x35"x61"	1825 lbs
SNG6-32024F	1.109-901.0	6.3	3200	7	15	KT6035R	575V	3 ph	18	507,000	64"x35"x61"	1825 lbs
SNG6-32024H	1.109-902.0	6.3	3200	7	15	KT6035R	208V	3 ph	39	507,000	64"x35"x61"	1825 lbs
SNG8-32024B	1.109-940.0	8	3200	9	20	KX9536R	230V	3 ph	46	658,000	64"x35"x61"	1840 lbs
SNG8-32024C	1.109-941.0	8	3200	9	20	KX9536R	460V	3 ph	26	658,000	64"x35"x61"	1840 lbs
SNG8-32024F	1.109-942.0	8	3200	9	20	KX9536R	575V	3 ph	26	658,000	64"x35"x61"	1840 lbs
SNG8-32024H	1.109-943.0	8	3200	9	20	KX9536R	208V	3 ph	52	658,000	64"x35"x61"	1840 lbs
SNG10-30024B	1.109-944.0	9.5	3000	11	20	KX1036R	230V	3 ph	52	816,000	64"x35"x61"	1910 lbs
SNG10-30024C	1.109-945.0	9.5	3000	11	20	KX1036R	460V	3 ph	26	816,000	64"x35"x61"	1910 lbs
SNG10-30024F	1.109-946.0	9.5	3000	11	20	KX1036R	575V	3 ph	26	816,000	64"x35"x61"	1910 lbs
SNG10-30024H	1.109-947.0	9.5	3000	11	20	KX1036R	208V	3 ph	60	816,000	64"x35"x61"	1910 lbs

\*PLEASE NOTE: Draft diverter required for ETL certification - PN 8.717-728.0 (8"); PN 9.801-040.0 (10"); PN 8.717-730.0 (12").

Also available in LP models.  
Ask for details on our SLP series.

**1.800.771.1881**  
www.SharkPW.com  
Sales@SharkPW.com  
Fax: 877-526-3246

